

## TECHNICAL DATASHEET

SAP No. 30006746 Article Description U-C-465g/m<sup>2</sup>-1250mm LEO

Textile Structure 7005667 LEO<sup>®</sup>

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	0 °	442 g/m <sup>2</sup>	+/- 5,0 %	TORAY T700SC F0E 12K
2	60 °	8 g/m <sup>2</sup>	+/- 5,0 %	E-glass 68 TEX
1	-60 °	8 g/m <sup>2</sup>	+/- 5,0 %	E-glass 68 TEX
Stitching		7 g/m <sup>2</sup>	+/- 2 g/m <sup>2</sup>	Polyester (PES) 83 dtex

### FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	tricot	Width (nominal)	1250 mm
Stitch length	2,60 mm	Total tolerance	+/- 5,4 %	Total areal weight	465 g/m <sup>2</sup>

**Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

**Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

**Storage** With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.