

## TECHNICAL DATASHEET

SAP No. 30005989 Article Description B-C-417g/m<sup>2</sup>-1270mm LEO

Textile Structure 7005929 LEO<sup>®</sup>

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
2	0 °	205 g/m <sup>2</sup>	+/- 5,0 %	TORAY T700SC F0E 12K
1	90 °	205 g/m <sup>2</sup>	+/- 5,0 %	TORAY T700SC F0E 12K
Stitching		7 g/m <sup>2</sup>	+/- 2 g/m <sup>2</sup>	Polyester (PES) 83 dtex

### FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	tricot-warp	Width (nominal)	1270 mm
Stitch length	2,60 mm	Total tolerance	+/- 5,4 %	Total areal weight	417 g/m <sup>2</sup>

**Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

**Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

**Storage** With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.