

TECHNICAL DATASHEET

SAP No. 30002262 Article Description X-S-E-1307g/m²-1270mm LEO

Textile Structure 7000650 LEO[®]

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	CSM	100 g/m ²	+/- 10,0 %	E-glass
2	45 °	597 g/m ²	+/- 5,0 %	E-glass 2.400 TEX
1	45 °	597 g/m ²	+/- 5,0 %	E-glass 2.400 TEX
Stitching		13 g/m ²	+/- 3 g/m ²	Polyester (PES) 83 dtex

FURTHER CHARACTERISTICS

Gauge	3,5	Stitching pattern	tricot	Width (nominal)	1.270 mm
Stitch length	4,50 mm	Total tolerance	+/- 5,4 %	Total areal weight	1307 g/m ²

Tracer yarn¹ 7 PC neon pink & tracer yarn 7 PC blue

¹Position can be determined individually

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.